

Rohre – Rohrbögen

DIN 2605

Andere Abmessungen, Formate und Güten auf Anfrage

Abmessung ä. Ø x Wand	Krümmungsdurchmesser mm in c ~ 3xdi	St35/St37.05	St35.8I
20,0 x 2,0	50 ± 5		
21,3 x 2,0	55 ± 5	●	
25,0 x 2,0	55 ± 5		
26,9 x 2,3	57 ± 5	●	
30,0 x 2,6	67 ± 5		
31,8 x 2,6	70 ± 5		
33,7 x 2,6	76 ± 5	●	
38,0 x 2,6	90 ± 5		
42,4 x 2,6	95 ± 5	●	
44,5 x 2,6	102 ± 5		
48,3 x 2,6	114 ± 6	●	
51,0 x 2,6	127 ± 6		
57,0 x 2,9	144 ± 6		
60,3 x 2,9	152 ± 6	●	
63,5 x 2,9	165 ± 6		
70,0 x 2,9	184 ± 6		
76,1 x 2,9	190 ± 6	●	
82,5 x 3,2	215 ± 6		
88,9 x 3,2	229 ± 6	●	
101,6 x 3,6	267 ± 6	●	
108,0 x 3,6	285 ± 6		
114,3 x 3,6	305 ± 6	●	
121,0 x 4,0	340 ± 10		
127,0 x 4,0	350 ± 10		
133,0 x 4,0	362 ± 6		
139,7 x 4,0	381 ± 8		
152,4 x 4,5	381 ± 10		
159,0 x 4,5	432 ± 8		
165,1 x 4,5	460 ± 8		
168,3 x 4,5	457 ± 8		
177,8 x 5,0	500 ± 10		
193,7 x 5,4	540 ± 8		

Abmessung ä. Ø x Wand	Krümmungsdurchmesser mm in c ~ 3xdi	St35/St37.05	St35.8I
216,0 x 6,0	610 ± 8		
219,1 x 6,3	610 ± 8		
244,5 x 6,3	680 ± 8		
267,0 x 6,3	756 ± 8		
273,0 x 6,3	762 ± 10		
298,5 x 7,1	840 ± 10		
318,0 x 7,5	910 ± 10		
323,9 x 7,1	914 ± 10		
355,6 x 8,0	1067 ± 20		
368,0 x 8,0	1067 ± 20		
406,4 x 8,8	1219 ± 20		
419,0 x 10,0	1219 ± 20		
457,2 x 10,0	1372 ± 30		
470,0 x 10,5	1345 ± 70		
508,0 x 11,0	1524 ± 70		
521,0 x 11,5	1495 ± 70		
558,8 x 12,5	1676 ± 70		
609,6 x 12,5	1828 ± 100		