

Stabstahl

Bandstahl in Stäben nach DIN EN 10048(ehem. DIN 1016), warmgewalzt, S235JRG2 (RSt37-2)

Andere Abmessungen, Formate und Güten auf Anfrage

Abmessung	schwarz	feuerverzinkt
10 x 2		
10 x 3		
10 x 4		
12 x 2		
12 x 3		
12 x 4		
15 x 2		
15 x 3	●	●
15 x 4	●	
16 x 2		
16 x 3		
16 x 4	●	
18 x 3		
18 x 4		
20 x 1		
20 x 2		
20 x 3	●	●
20 x 4	●	●
25 x 1		
25 x 2		
25 x 3	●	●
25 x 4	●	●
30 x 1		
30 x 2		
30 x 3	●	●
30 x 4	●	●
35 x 3	●	●
35 x 4	●	●
40 x 2		
40 x 3	●	●
40 x 4	●	●
45 x 3		

Abmessung	schwarz	feuerverzinkt
45 x 4		
50 x 2		
50 x 3	●	●
50 x 4	●	●
55 x 3		
55 x 4		
60 x 2		
60 x 3	●	
60 x 4	●	●
70 x 3	●	
70 x 4	●	
80 x 2		
80 x 3	●	
80 x 4	●	●
90 x 3		
90 x 4		
100 x 3	●	●
100 x 4	●	●
110 x 3		
110 x 4		
110 x 5	●	
110 x 6	●	
120 x 3		
120 x 4	●	
120 x 5	●	●
120 x 6	●	●
130 x 3		
130 x 4		
130 x 5	●	
130 x 6	●	●
140 x 3		
140 x 4		
140 x 5	●	●
140 x 6	●	●

Abmessung	schwarz	feuerverzinkt
150 x 3		
150 x 4		
150 x 5	●	●
150 x 6	●	●

Stabstahl

Bandstahl in Ringen nach DIN EN 10058 bzw. DIN EN 10048, warmgewalzt, S235JRG2 (RSt37-2)

Andere Abmessungen, Formate und Güten auf Anfrage

Abmessung	50 kg, feuerverzinkt	25 kg, feuerverzinkt
20 x 2		
20 x 3		
25 x 2		
25 x 3		
25 x 4		
30 x 2		
30 x 3		
30 x 3,5	●	●
30 x 4		
40 x 3		
40 x 4		
40 x 5		